

The Smoothest Ride in Travel Mobility



3-wheel

GO GO®
LX WITH CTS SUSPENSION



4-wheel

The **Go-Go**® LX with **Comfort-Trac Suspension (CTS)** offers a whole new level of comfort and performance. This industry-first CTS technology incorporates advanced suspension for improved absorption over various terrains. The Go-Go® LX with CTS offers a 300 lb. weight capacity, a per charge range up to 10.5 miles and a maximum speed of 4.4 mph. Standard features include feather-touch disassembly, a wraparound delta tiller with charger port, black, non-scutting tires, LED headlight and front basket. Optional color shrouds available.



Comfort-Trac Suspension

PRIDE® MOBILITY SCOOTERS
LIVE YOUR BEST®

| pridemobility.com |



Specifications 3W: S50LX 4W: S54LX

| | |
|---|---|
| Weight Capacity | 300 lbs. |
| Maximum Speed ¹ | Up to 4.4 mph |
| Ground Clearance ² | 1.5" at motor |
| Turning Radius ² | 3W: 33" 4W: 44.75" |
| Overall Length ² | 3W: 39.75" 4W: 41" |
| Overall Width ² | 20.5" |
| Front Tires | 3W: 2" x 8" solid 4W: 2" x 7" solid |
| Rear Tires | 2.5" x 8" solid |
| Range Per Charge ^{1,4} | 3W: Up to 5.9 miles (12 AH) 4W: Up to 5.5 miles (12 AH) 3W: Up to 9.4 miles (18 AH) 4W: Up to 11 miles (18 AH) |
| Total Weight Without Batteries ⁵ | 3W: 85 lbs. 4W: 87 lbs. |
| Heaviest Piece When Disassembled | 3W: 34 lbs. (front section) 4W: 37 lbs. (front section) |
| Standard Seating | Type: Foldable, compact, vinyl-covered, molded plastic Weight: 23 lbs. Material: Black Vinyl Dimensions: Width: 17" Depth: 17" |
| Motor Output | 24-volt DC motor, sealed mini-transaxle |
| Brakes | Regenerative and electromechanical |
| Battery Requirements ^{3,5} | (2) 12V Deep-cycle Size: (2) 12 AH-9 lbs. each or (2) 18 AH (optional)-14lbs. each Weight: 12 AH: 20 lbs. per battery pack, 18 AH: 29.5 lbs. per battery pack |
| Battery Charger | Off-board, 2 amp |
| Colors | Interchangeable shrouds |

Optional:



Orion Yellow



Onyx Black



Pearl Pink



Sunburst Orange

Features

- Charger port in tiller
- Comfort-Trac front and rear suspension for added comfort
- Convenient dual voltage charger can charge battery pack on-board or off-board
- Feather-touch disassembly permits simple frame separation with only one hand and easily disassembles into 5 lightweight pieces for convenient transport and storage
- Front frame-mounted seat post offers maximum stability
- Includes two sets of easily changeable, red and blue colored panels
- Long-lasting, high-intensity, front LED headlight offers optimal pathway illumination
- Microprocessor-based controller offers optimal power management and added safety features
- Pride's exclusive black, non-scuffing tires
- Standard front tiller-mounted basket

Accessories

- Additional 12AH battery box
- Additional 18AH battery box
- Cane clip attachment
- Cane/crutch holder (single, double)
- Cell phone holder
- Cup holder
- Forearm crutch holder
- 50" Lap belt
- Oxygen tank holder
- Rear basket
- Rearview mirror
- Saddlebag
- Safety flag
- Under seat storage (assembly required)
- Walker holder
- Weather cover
- Wishbone crutch holder
- XLR USB charger

Military Patches



LIFT FINDER

Pride offers a variety of lifts to **transport your mobility product with ease**. To find a compatible lift for your vehicle and mobility product, use our new Lift Finder application at pridemobility.com/lift-finder/

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).

² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³ AGM or gel cell type required.

⁴ Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.