

# Comfort and Performance for your Active Lifestyle



3-Wheel



4-Wheel

**VICTORY® 9**

The **Victory®** series line of mobility scooters offer a perfect balance of style, comfort and performance for your active lifestyle. The Victory® 9 features one-hand feather touch disassembly, wraparound delta tiller, 300 lb. weight capacity, a per charge range up to 13 miles and a maximum speed up to 5.25 mph. Standard features include, 9" solid tires, LED pathway light, backlit battery gauge and a front basket. Available in Viper Blue and Candy Apple Red.



PRIDE® **MOBILITY SCOOTERS**  
LIVE YOUR BEST®

| [pridemobility.com](http://pridemobility.com) |





## Specifications 3W:SC609 4W:SC709

Weight Capacity	300 lbs.
Maximum Speed <sup>1</sup>	Up to 5.3 mph
Ground Clearance <sup>3</sup>	3W: 2" 4W: 2.25"
Turning Radius <sup>3</sup>	3W: 40.25" 4W: 51.5"
Overall Length <sup>3</sup>	3W: 43.5" 4W: 45.5"
Overall Width <sup>3</sup>	3W: 22.25" 4W: 25.5"
Seat-to-Ground Height	19.25"-20.75"
Seat-to-Deck Height	17.25"-18.75"
Front Tires	3W: 3" x 8" solid 4W: 3" x 9" solid
Rear Tires	3" x 9" solid
Suspension	N/A
Range Per Charge <sup>1,2</sup>	Up to 13 miles
Total Weight Without Batteries <sup>3,7</sup>	3W: 117 lbs. 4W: 131 lbs.
Heaviest Piece When Disassembled <sup>3</sup>	3W: 48.5 lbs. (front section) 4W: 59 lbs. (front section)
Standard Seating	Foldable molded plastic Weight: 28 lbs. Material: Black Vinyl Dimensions: 18" width, 17" depth
Drive System	Rear-wheel drive, sealed transaxle with 24-volt DC motor
Dual Braking System	Electronic, regenerative and electromechanical
Battery Requirements <sup>3,4,5</sup>	Size: (2) U-1(12V deep-cycle) standard Weight: 24 lbs. each
Battery Charger	3.5-amp, off-board
Colors	  Candy Apple Red Viper Blue

## Features

- Exclusive one-hand feather touch disassembly provides the ultimate quick transport system
- Auto-connecting front-to-rear harness
- Delta tiller with wraparound handles
- Exclusive stylish, lightweight, non-scuffing, black, low-profile tires
- Backlit battery gauge
- Long-lasting, high-intensity LED headlight offers optimal pathway illumination
- Lightweight pinchless hinge seat eight position rotation, sliders and viscoelastic foam inserts for increased comfort
- Easy-grip tiller adjustment knob
- Easy access tiller-mounted charger port

## Accessories

- Forearm crutch holder
- Wishbone crutch holder
- Quad cane holder
- Cane/crutch holder (3" single, 3" double)
- Double crutch holder
- Oxygen tank holder
- Cup holder
- Rear basket
- Safety flag
- Walker holder
- Rearview mirror
- Weather cover
- Saddlebag
- Cell phone holder
- XLR USB charger
- Lap belt (50", 60", 70")

## Military Patches



## LIFT FINDER

Pride offers a variety of lifts to **transport your mobility product with ease**. To find a compatible lift for your vehicle and mobility product, use our new Lift Finder application at [pridemobility.com/lift-finder/](http://pridemobility.com/lift-finder/)

<sup>1</sup> Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.

<sup>2</sup> Tested in accordance with ANSI/RESNA, MC Vol2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

<sup>3</sup> Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.

<sup>4</sup> AGM or gel cell type required.

<sup>5</sup> Battery weight may vary based on battery manufacturer.

<sup>6</sup> Includes standard seat weight.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.