

and Performance







in Viper Blue

4-Wheel shown in Candy Apple Red

> The Victory® 10 series offers added style, comfort and performance for your active lifestyle. Standard features include LED pathway light, LED battery meter, feather touch disassembly, wraparound delta tiller, 10" solid tires and a front basket. A 400 lb. weight capacity, a per charge range of up to 16 miles and a maximum speed up to 5.3 mph compliment the versatility of the Victory 10. Available in Viper Blue and Candy Apple Red.











Specifications 3W:SC610 4W:SC710

| Weight Capacity | 400 lbs. |
|--|---|
| Maximum Speed ¹ | Up to 5.3 mph |
| Ground Clearance ³ | 3W: 2.2" at motor, 1.26" at anti-tip 3.4" at side deck 4W: 2" at motor, 1.5" at anti-tip 3.1" at side deck |
| Turning Radius³ | 3W: 42" 4W: 54" |
| Overall Length ³ | 3W: 45.25" 4W: 47" |
| Overall Width³ | 22.25" |
| Seat-to-Ground Height | 20.5"-22" |
| Seat-to-Deck Height | 17.5″-19″ |
| Front Tires | 3.5" x 10" solid |
| Rear Tires | 3.5" x 10" solid |
| Suspension | N/A |
| Range Per Charge ^{1,2} | Up to 16 miles |
| Total Weight Without Batteries ^{3,7} | 3W: 133 lbs. 4W: 137 lbs. |
| Heaviest Piece When Disassembled ³ | 3W: 54 lbs. (front section) 4W: 61 lbs. (front section) |
| Standard Seating | Type: Foldable molded plastic Weight: 28 lbs. Material: Black Vinyl Dimensions: 18" width, 17" depth |
| Drive System | Rear-wheel drive sealed transaxle with 24-volt DC motor |
| Dual Braking System | Electronic, regenerative and electromechanical |
| Battery Requirements ^{3,4,5} | Size: (2) U-1 standard, Weight: 24 lbs. each Size: (2) 40 AH (optional), Weight: 32 lbs. each |
| Battery Charger | 3.5-amp, off-board (U-1), 5-amp, off-board (40 AH) |
| Colors | |

Candy Apple Red Viper Blue

HCPC Code: K0801 (Group 1, Heavy Duty)

- 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.
- 2 Tested in accordance with ANSI/RESNA, MC Vol2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 3 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
- 4 AGM or gel cell type required.
- 5 Battery weight may vary based on battery manufacturer.
- 6 Includes standard seat weight.

Features

- A standard front basket provides ample storage
- Feather-touch disassembly permits simple frame separation with only one hand for easy transport and storage
- Charger port located on the tiller enables you to conveniently charge your scooter
- Delta tiller with ergonomic wraparound handles enables easy-to-use left or right hand operation and the ability to rest your wrist on the handle for added comfort
- Easy-to-read LED battery meter
- Exclusive stylish, lightweight, non-scuffing, black, lowprofile tires
- Long-lasting, maximum-intensity LED headlight offers optimal pathway illumination
- Lightweight pinchless hinge seat eight position rotation, sliders and viscoelastic foam inserts for increased comfort
- Easy-grip tiller adjustment knob

Accessories

- Cane clip attachment
- Cane/crutch holder (single, double)
- Cell phone holder
- Cup holder
- Forearm crutch holder
- 50", 60", 70" Lap belt
- Oxygen tank holder
- Rear basket
- Rearview mirror
- Saddlebag
- Safety flag
- Walker holder
- Weather cover
- XLR USB charger

ptions

40 AH batteries with 5-amp, off board charger

Optional Seating

- Limited recline, black vinyl, high back with height adjustable headrest, flip-up height and width adjustable armrests
 - * 18" x 18" (sliders) * 20" x 20" (no sliders) * 22" x 18" (no sliders)
- Deluxe contour high back black vinyl with height adjustable headrest, flip-up height and width adjustable armrests (no sliders)
 - 18" x 18" 18"x 20" 20" x 20" 22" x 20"

Military Patches





Find a compatible lift for your vehicle online: PRIDEMOBILITY.COM/LIFT-FINDER

NOTE: All specifications subject to change without notice The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or -3 %. Dimensions listed are for scooter only. Overall measurements will vary based on seating and accessory selections









